




INNOVATIONS FOR LIVING®

# QuietR® Duct Liner Pressure Loss Performance

## Product Data Sheet



This chart is to be used in place of the standard friction chart published in the ASHRAE *Handbook of Fundamentals*. For conversion of round equivalents to rectangular sizes, use Table 2, "Equivalent Rectangular Duct Dimensions" from the same reference. Tests conducted in accordance with NAIMA AHS-152T.

### To convert to metric values:

Flow Rate	Multiply cfm by 0.000472 to obtain m <sup>3</sup> /s.
Velocity	Multiply fpm by 0.00508 to obtain m/s.
Pressure Loss	Multiply in. w.g. /100 ft of duct by 8.164 to obtain Pa/m of duct.
Diameter	Multiply inches by 25.4 to obtain millimeters.

### Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Nothing contained in this bulletin shall be considered a recommendation.



INNOVATIONS FOR LIVING®

**OWENS CORNING INSULATING SYSTEMS, LLC**  
ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO, USA 43659

**1-800-GET-PINK®**

[www.owenscorningcommercial.com](http://www.owenscorningcommercial.com)

Pub. No. 10012934-A. Printed in U.S.A. May 2012. THE PINK PANTHER™ & ©1964–2012 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2012 Owens Corning. All Rights Reserved.

